

# Ergonomic Mobile Drum Lifter

## The stress reliever for drum handling operations

SERVOLIFT has manufactured over 1300 of these machines to-date. The strange looking unit is the result of full optimization for drum handling. When handling a 250Kg load, the unit requires only ~13-lbs for pushing force to reverse the rear swivel wheels and ~8-Lbs thereafter to move it around. Grab, Lift, & Tip (anywhere between 0-180°). Ideal for manual scooping powders from drums or anywhere you need to move heavy drums.



## The Advantage: Proven Designs - Fully Customized - Unmatched Experience

## Profile

Available in manually pushed and self propelled versions. With battery, pneumatic or plug-in electric power.

Designed for all drum types: fiber, plastic and steel.

Powered functions: Grab, Lift, Invert (180 deg) & Drive.

Meets or exceeds FDA and USDA requirements.

Offered in all grades of stainless steel or painted carbon steel.

Explosion proof option for all classified areas

### **System Features**

All Models power grab, lift and freely invert drums between 0-180°

The Model SLN is a miniature unit of the SL 150 & SL 250 units

Model SLD 250 has a rotatable base for operations in tight areas (can work like a stationary unit).

The model SLF has a powered self propulsion system.

The 150 designates 330 lbs capacity and the 250 550 lbs. Optionally we can offer 660 lbs capacity.

#### Power

• Your choice: Battery, Air or Plug-in Electrical. General Purpose or Class 1/2, Division 1/2 Explosion Proof

#### Materials of Construction

- 304 Stainless Steel welds continuous and ground smooth. Entire unit polished to a #4 luster, polish grain in uniform directions for a professional look.
- Non-Marking wheels with stainless housings. Wheels in white Plastic.

#### **Other Advantages**

- Most GMP drum lifter on the market
- Most proven design manufactured since 1977 the design is perfected

Model	А	В	С	D	E	F	G	Н	I
SL-250	133.9″	66.8″	113.3″	59.3″	46.8″	18.5″	35.4″	34.3″	-
SLD-250	135.8″	68.7″	115.3″	61.6″	45.4″	16.9″	35.4″	36.2″	18.4″
SLF-250	133.8″	66.8″	113.3″	60.5″	60.5″	19.8″	35.4″	34.2″	-
SLN-150	79.9″	58.7″	77.2″	48.3″	46.8″	20.1″	35.4″	32.6″	_











