





Ice-O-Matic
lce. Pure and Simple

TABLE OF CONTENTS

| About Ice-O-Matic General Information | |
|--|----|
| Model Number Guide Ice Form Series Guide | 2 |
| UCG Gourmet Ice™ Undercounters | 11 |
| ICE Series Cube Ice™ Undercounters ICE Series Cube Ice Makers ICE Series Cube Ice Makers - Accessories | 13 |
| Elevation Series Cube Ice TM Elevation Features Elevation Series Cube Ice Makers - 22" Modular Elevation Series Cube Ice Makers - 30" Modular Elevation Series Cube Ice Makers - 48" Modular Elevation Series Modular - Accessories | 14 |
| GEM Series Pearl Ice TM GEM Series Pearl Ice® Makers - Modular GEM Series Pearl Ice® Makers / Ice & Water Dispensers GEM Series Pearl Ice® Makers - Accessories | 20 |
| MFI Series™ Flake Ice™ MFI Series Flake Ice Makers - Modular MFI Series Flake Ice Makers - Accessories | 23 |
| Remote Condensers & Accessories Countertop & Hotel Ice Dispensers Ice Dispenser Accessories & Kits Storage Bins & Accessories Ice Machine & Bin Configurations ICE Series Cube Ice Makers - Accessories | 24 |
| Pricing Contact Us | 32 |



About us.

Located in Denver, Colorado, Ice-O-Matic is a leading American manufacturer of a wide range of commercial ice-making products including cube ice makers, Pearl Ice® ice makers, flake ice makers, storage bins, dispensers and water filters.



ICE WITH A CLEAR CONSCIENCE

Sustainability

Ice-O-Matic offsets the carbon footprint of its Denver factory by using recycled packaging materials. We also recycle our industrial and office waste products.

Made in the U.S.A.

A U.S.-based company with over 200 employees worldwide, Ice-O-Matic provides and creates American jobs. Ice-O-Matic is committed to producing quality products, and to the hundreds of employees who make it happen. Ice-O-Matic products are designed and assembled in America.

ENERGY STAR®

Ice-O-Matic partners with ENERGY STAR and is dedicated to improving energy efficiency. Each ENERGY STAR certified ice maker can save businesses energy and money on their utility bills. When considering batch-type ice makers, ENERGY STAR certified systems can save, on average, about 1,200 kwh annually, or \$125/year in electricity bill costs.


TERMS & CONDITIONS

- Specifications and prices are subject to change without notice.
- All height dimensions of bins and ice makers with built-in storage include the height of the legs where applicable.
- For a full listing of Terms and Conditions, visit: www.iceomatic.com

OUR HISTORY

Perfecting Ice Since 1952®

Since 1952, Ice-O-Matic has worked tirelessly on developing, enhancing and perfecting the way ice is made. Founder Dave Smith's mission was to offer the best ice machines in the business with a single-minded focus on top-quality ice. To this day, Ice-O-Matic is dedicated to providing simple, reliable and easy-to-use commercial ice machines.



INSTALLATION CONSIDERATIONS

Allow enough space for the following elements


- The ice maker, bin and water filter
- Airflow

Utilities

- What are the voltage and amperage characteristics of the electrical outlet that will be used for this ice maker?
- Is there a floor drain within 6 feet (1.8 meters)?
- Is there a water source with water shutoff?
- Are the utilities within 6 feet (1.8 meters) of the ice-maker location?

Remote installation

- Is there an outdoor condenser location available?
- Is there easy roof access and penetration?
- Maximum precharged tubing line run considerations?





SIZING YOUR ICE MAKER

- Does the existing ice maker meet peak usage during the hottest time of the year?
- Where are the various ice stations in the establishment that will need ice?
- Will multiple ice stations be serviced from one or multiple ice makers?
- For future growth, consider building in at least 20 percent additional ice capacity on new installations.
- For dispenser applications, increase machine production by 50%

APPROXIMATE ICE USAGE PER DAY

Restaurant 1.5 lbs. per person or 6 lbs. per seat Cocktail 3 lbs. per person 5 oz. per 7-10 oz. drink 8 oz. per 12-16-oz. drink 12oz. per 18-24-oz. drink

| LODGING | |
|-----------|------------------|
| Guest Ice | 5 lbs. per room |
| Catering | 1 lb. per person |

NOTE: The charts above outlines the approximate required ice amount per day, depending on application usage.

WARRANTY

ICE MAKER WARRANTY

Every Ice-O-Matic ice maker is backed by a warranty that provides both parts and labor coverage. To register products, view the warranty details or check your warranty status, visit the "Warranty Registration" page at: iceomatic.com/warranty.

Cube Ice Makers - CIM and Ice Series

- Three years parts and labor
- Five years parts on evaporators and compressors
- Seven years parts on evaporators with IOM filter program (U.S.A. and Canada only)

Flake Ice Makers - MFI Series

- Three years parts and labor
- Five years parts coverage on the compressor

Pearl Ice® Makers - GEM Series

- Modular three years parts and labor
- Countertop dispenser two years parts and labor
- Modular/dispenser five years parts coverage on the compressor
- GEMU090 undercounter one years parts and labor

Remote Condensers - RC Series

• Three years parts and labor

Gourmet Ice Makers - UCG Series

• Three years parts and labor

Dispensers - CD and IOD Series

- IOD countertop dispensers two years parts warranty and one year labor warranty
- CD hotel dispensers three years parts and labor warranty

Storage Bins

• Two years parts and labor

Water Filter Manifold Systems

• One year parts and labor (excluding cartridges)

Accessories

• 90 days parts only

Residential Installation

 All commercial machines installed in residential applications have one year parts and labor warranty


WATER FILTRATION PROGRAM

- Buy a new Ice-O-Matic IFQ Series Water Filtration System with a new CIM Series™ Cube Ice Maker, replace the filter cartridge every six months and Ice-O-Matic will extend the limited cuber evaporator warranty to seven years parts and labor.
- New ice maker and filter must be installed at the same time.
- Must register both the ice maker and water filter online at iceomatic.com/warranty within five days of installation.
- Water filter cartridge model number and serial number must be included with registration information.
- Water filter changes must be recorded at iceomatic.com every six months or less.
- Replacement cartridge must be an Ice-O-Matic replacement cartridge (See sizing chart for cartridge requirements).
- Available in the U.S.A. and Canada only.

EXTEND YOUR WARRANTY BY PARTICIPATING IN OUR WATER FILTRATION PROGRAM!



For more information on water filters, see page #30



MODEL NUMBER GUIDE

| Elevation Series™ - Cube Ice | | | | |
|------------------------------|-----|---|--|--|
| CIM 05 3 CIMO530HA90 0 | CIM | Model CIM = Cube Ice Modular Series | | |
| | 05 | Basic Family Size (lbs/24 hr): 03 = 300 lbs, 04 = 400 lbs, 10 = 1000 lbs plus | | |
| | 3 | Width of machine in inches: 3 for 30", 2 for 22", 4 for 48" | | |
| | 0 | Unit Electrical Characteristics: 0, 5, 6, 7 *** | | |
| | Н | Cube Type: H = Half, F = Full, G = Grande | | |
| А | | Condenser Type: A = Air, W = Water, R = Remote | | |
| | 90 | Refrigerant: 49 = R449, 90 = R290 | | |
| | | | | |

| UCG Series - Gourmet Ice Makers | | | | | |
|---------------------------------|---|---|--|--|--|
| | UCG | Undercounter Gourmet Series | | | |
| 06 | Basic Family Size (lbs/24 hr): 06 = 60 lbs, 08 = 80 lbs, 10 = 100 lbs, 13 = 130 lbs | | | | |
| UCG060A | 0 | Unit Electrical Characteristics: 0, 5, 6, 7 *** | | | |
| | G | Cube Type: G = Gourmet, GG = Gourmet Grande | | | |
| | А | Condenser Type: A = Air Cooled | | | |

| Pedri ICe" & Flake ICe Makers | | | | | |
|-------------------------------|-----|--|--|--|--|
| 09 | GEM | Model GEM = Modular Pearl Ice®, Model MFI = Modular Flake Ice Series | | | |
| | 095 | Basic Family Size (lbs/24 hr): Approximately 950 lbs | | | |
| GEM0956A | 6 | Unit Electrical Characteristics: 0, 5, 6, 7 *** | | | |
| | А | Air Cooled, W = Water Cooled, R = Remote Condenser | | | |


| Remote Condensers | | | | | |
|--------------------|----|---|--|--|--|
| RC 20 RC206C49 6 C | RC | Remote Condensers | | | |
| | 20 | Coil Size | | | |
| | 6 | Unit Electrical Characteristics: 0, 6 *** | | | |
| | С | C = Cuber Remote Condenser, G = GEM or MFI Remote Condenser | | | |
| | 49 | Refrigerant: 40 = R404A, 49 = R449 | | | |

| Storage Bins | | |
|--------------|----|------------------------------------|
| DEE | В | Model B = Bin |
| B55 | 55 | Approx. Size: 55 = 550-lb capacity |

| Water Filter Systems | | | | |
|----------------------|--|--|--|--|
| IFI4C | IFI Filter Type: IFI = Ice-O-Matic Filter, inline type | | | |
| 1F14C 4 | | Fitting Size: 4 = 1/4", 8 = 3/8" | | |
| IFQ1 | IFQ | Filter Type: IFQ = Ice-O-Matic Filtration System, IFQ Series | | |
| IFWI | 1 | Number of Cartridges: 1 = Single, 2 = Double | | |

^{***} Unit Electrical Characteristics

0 - 115/60/1 5 - 220-240/50/1 6 - 208-230/60/1 7 - 208-230/60/3



ICE FORMS & SERIES GUIDE

Gourmet Series[™] - Undercounters



Gourmet (G) (H) 11/4 in (Dia.) 1 in



Gourmet Grande (GG)
(H) 11/2 in
(Dia.) 11/2 in

Pearl Ice® Makers



Pearl (P) (H) **1/2** in

(Dia) **3/8** in



Flake Ice Makers

Flake (F)

ELEVATION Series™ Cube Ice Makers - Modular



Half (H)

(H) **7/8** in

(W) **3/8** in

(D) **7/8** in



Full (F)

(H) **7/8** in

(W) **7/8** in

(D) **7/8** in



Grande (GR)

(H) 11/8 in

(W) 11/4 in

(D) **7/8** in

Ice Series™ Cube Ice Makers & Undercounters



Half (H)

(H) **7/8** in

(W) **3/8** in

(D) **7/8** in



Full (F)

(H) **7/8** in

(W) 7/8 in

(D) **7/8** in



UCG Series™ - Undercounters



| Model Number | Machine Height Standard/Short Leg (in) | Ice Production Ibs/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Bin Storage (lbs) | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|--|--|--|-------------------------|--------------------|------------------|-------------------------|
| UCG060A | 30.25-32 / 27.375-27.75 | 63 | 45 | 17.5 | Air | 115/60/1 | 81.5 |



| Model Number | Machine Height Standard/Short Leg (in) | Ice Production Ibs/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/ 24 hr @ 90°F Air/ 70°F Water | Bin Storage (lbs) | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|--|--|--|-------------------------|--------------------|------------------|-------------------------|
| UCG080A | 32.25-34 / 29.375-29.75 | 95 | 77.8 | 33 | Air | 115/60/1 | 81.5 |




| Model Number | Machine Height Standard/Short Leg (in) | Ice Production Ibs/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Bin Storage (lbs) | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|--|--|--|-------------------------|--------------------|------------------|-------------------------|
| UCG100A | | 114 | 91.7 | | | | |
| UCG130A | 36-37.75 / 33.125-33.5 | 121 | 114.3 | 48.5 | Air | 115/60/1 | 97 |
| UCG130GA* | | 121 | 100.5 | | | | |

^{*} Gourmet Grande

UCG Series[™] - Accessories

| Model Number | Description | Ship Weight (lbs) |
|--------------|--|-------------------|
| 1011411-87 | True undercounter leg for UCG100, UCG130 and UCG130GA | 4 |



ICE Series[™] - Undercounters



| Model Number | Ice Production Ibs/ 4 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half or Full Cube | Bin Storage (lbs) | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|--|--|----------------------|-------------------------|--------------------|------------------|----------------------|
| ICEU220A | 238 | 165 | 11/⊏ | 74 | Air | 115/60/1 | 160 |
| ICEU226A | 241 | 166 | H/F | 74 | Air | 208- 230/60/1 | 160 |



| Model Number | Ice Production Ibs/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half Cube | Bin Storage (lbs) | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|--|--|--------------|-------------------------|--------------------|------------------|----------------------|
| ICEU300A | 309 | 228 | H/F | 112 | Air | 115/60/1 | 206 |

ICE Series™ - Ice Makers Bin Thermostat Kit Included



| Model Number | Ice Production Ibs/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half Cube | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|--|--|--------------|--------------------|------------------|----------------------|
| ICE1506HT | 1430 | 1125 | Н | Air | 208-230/60/1 | 310 |
| ICE1506HT49 | 1310 | 1070 | Н | Δir | 208-230/60/1 | 310 |



| Model Number | Ice Production Ibs/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half Cube | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|--|--|--------------|--------------------|------------------|----------------------|
| ICE1506HR* | 1450 | 1100 | Н | Remote | 208-230/60/1 | 310 |
| ICE1506HR49* | 1228 | 1028 | Н | Remote | 208-230/60/1 | 310 |

^{*} Remote condensers and line sets are required for remote-cooled ice makers. See Page 24 & 25 for Remote Condensers.

ICE Series™ - Accessories

| Model Number | Description | Ship Weight (lbs) |
|-----------------|--|-------------------|
| BPF-1 | Filler Panel Kit for 30" ICE Series™ Cube Ice Makers for B110 bins only | 8 |
| KBT5 | Bin Top for 30" ICE1506 family for B100 only | 30 |
| KCUBEDISP | Bin-level kit required for dispensing application | 1 |
| KBTF21506* | Bin Top for (2) ICE1506's on 60" bins only | 43 |

^{*} Additional adapters may be required from dispenser manufacturer





Dual Exhaust

Allows hot-air discharge from the side and/or the top of every unit for flexibility.

Just one side needs at least 6 inches of clearance for the machine to reach full ice production.



Snap in and out plastic parts

Sanitation has never been easier. Parts snap in and out and are dishwasher safe up to 180°F, no bottle brushes or tools required.



Robust Evaporator

With a 1 mil thick nickle-plated copper evaporator, our CIM series is reliable and robust. The evaporator is the heart of the ice machine and it's durability is defines the life of the machine



One-Touch Cleaning

One touch to de-scale, one touch to sanitize. LEDs signal when cleaning is required. It takes less than an hour to deep clean a CIM ice machine.



Safe Ice Kit - KSI-1

The Safe Ice purification system passively eliminates contaminants throughout your Ice-O-Matic machine by recirculating anti-microbial ozone infused air.

The Elevation Series.

Our Elevation Series is designed to simplify life. Our cube ice machines are easy to clean, easy to service, simple to operate, and environmentally responsible without sacrificing productivity. The Elevation Series provides clean, dependable ice from an astonishingly user-friendly and energy-efficient machine designed to work as hard as you. We believe design simplicity equals operational excellence, and innovation goes beyond just adding bells and whistles.



ELEVATION SERIES™ | Modular Ice Makers



| Model Number | Ice Production lbs/24 hr @70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half or Full Cube | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|---|--|-------------------------|--------------------|------------------|----------------------|
| CIM0320A90 | 325 | 240 | ц/г | Air | 115/60/1 | 125 |
| CIM0520A90 | 525 | 400 | H/F | Air | 115/60/1 | 132 |



| Model Number | Ice Production Ib/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half or Full Cube | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|---|--|-------------------------|--------------------|------------------|----------------------|
| CIM0826A49 | 850 | 711 | | Air | 208- 230/60/1 | 230 |
| CIM0826R49* | 850 | 759 | H/F | Remote | | 220 |
| CIM1126A49 | 960 | 740 | П/Г | Air | | 230 |
| CIM1126R49* | 930 | 820 | | Remote | | 215 |



| | Model Number | Ice Production lb/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half or Full Cube | Condens- ing Unit | Voltage Units | Ship Weight (lbs) |
|--|-----------------|---|--|----------------------|----------------------|---------------|----------------------|
| | CIM0330A90 | 325 | 240 | /= | Air | 115/60/1 | 145 |
| | CIM0430A90 | 435 | 312 | | Air | 115/60/1 | 145 |
| | CIM0530A90 | 525 | 400 | | Water | 115/60/1 | 155 |
| | CIM0530R49* | 500 | 442 | H/F | Air | 115/60/1 | 173 |
| | CIM0636A90 | 600 | 491 | | Air | 208-230/60/1 | 163 |
| | CIM0636R49* | 610 | 528 | | Remote | 208-230/60/1 | 165 |



| Model Number | Ice Production Ib/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half or Full Cube | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|---|--|-------------------------|--------------------|------------------|----------------------|
| CIM0836A49 | 850 | 711 | | Air | 208- 230/60/1 | 230 |
| CIM0836R49* | 850 | 759 | 11/⊏ | Remote | | 220 |
| CIM1136A49 | 960 | 740 | H/F | Air | | 230 |
| CIM1136R49* | 930 | 820 | | Remote | | 215 |



| Model Number | Ice Production Ib/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half or Full Cube | Condens- ing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|---|--|----------------------|----------------------|------------------|----------------------|
| CIM1446A49 | 1600 | 1308 | Н/Г | Air | 208- 230/60/1 | 310 |
| CIM1446R49* | 1609 | 1212 | | Remote | 208- 230/60/1 | 318 |
| CIM2046R49* | 1830 | 1502 | | Remote | 208- 230/60/1 | 329 |

^{*}See Page 24 for Remote Condensers

ELEVATION SERIES™ | Modular Ice Makers



| Model Number | Ice Production Ibs/24 hr @70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half or Full Cube | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|---|--|-------------------------|--------------------|------------------|----------------------|
| CIM0320A | 313 | 244 | H/F | Air | 115/60/1 | 150 |
| CIM0320W | 316 | 274 | | Water | 115/60/1 | 150 |
| CIM0326A | 330 | 236 | | Air | 208- 230/60/1 | 150 |
| CIM0520A | 561 | 432 | | Air | 115/60/1 | 165 |
| CIM0520W | 586 | 533 | | Water | 115/60/1 | 175 |
| CIM0526A | 555 | 419 | | Air | 208- 230/60/1 | 165 |



| Model Number | Ice Production Ib/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half or Full Cube | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|---|--|-------------------------|--------------------|------------------|----------------------|
| CIM0826A | 896 | 711 | | Air | | 230 |
| CIM0826W | 896 | 774 | | Water | 208- 230/60/1 | 230 |
| CIM0826R* | 906 | 793 | /⊏ | Remote | | 220 |
| CIM1126A | 932 | 762 | H/F | Air | | 230 |
| CIM1126W | 968 | 851 | | Water | | 240 |
| CIM1126R* | 968 | 830 | | Remote | | 215 |



| | Model Number | Ice Production Ib/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half or Full Cube | Condens- ing Unit | Voltage Units | Ship Weight (lbs) |
|------|-----------------|---|--|----------------------|----------------------|---------------|----------------------|
| | CIMO330A | 313 | 224 | | Air | 115/60/1 | 145 |
| 1/4" | CIM0330W | 316 | 265 | | Water | 115/60/1 | 145 |
| | CIMO430A | 435 | 310 | | Air | 115/60/1 | 155 |
| (| CIMO430W | 460 | 365 | | Water | 115/60/1 | 155 |
| | CIMO436A | 465 | 340 | | Air | 208-230/60/1 | 155 |
| | CIMO436W | 500 | 405 | / | Water | 208-230/60/1 | 155 |
| | CIM0530A | 561 | 420 | H/F | Air | 115/60/1 | 155 |
| | CIM0530W | 586 | 470 | | Water | 115/60/1 | 155 |
| | CIM0530R* | 525 | 405 | | Remote | 115/60/1 | 160 |
| | | 600 | 440 | | Air | 208-230/60/1 | 160 |
| | CIM0636W | W 620 535 | | Water | 208-230/60/1 | 160 | |
| | | 615 | 520 | | Remote | 208-230/60/1 | 160 |
| | | | | | | | |

Qualifies for Energy Star

^{*}See Page 25 for Remote Condensers

ELEVATION SERIES™ | Modular Ice Makers



| Model Number | Ice Production Ib/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half /Full/ Grande Cube | Condens- ing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|---|--|-------------------------------|----------------------|------------------|-------------------------|
| CIM0836A | 896 | 668 | | Air | 208-230/60/1 | 220 |
| CIM0836W | 896 | 798 | H/F | Water | 208-230/60/1 | 210 |
| CIM0836R* | 906 | 769 | | Remote | 208-230/60/1 | 220 |
| CIM0836GA** | 800 | 645 | GR | Air | 208-230/60/1 | 230 |
| CIM1136A | 932 | 739 | | Air | 208-230/60/1 | 220 |
| CIM1136W | 968 | 896 | H/F | Water | 208-230/60/1 | 225 |
| CIM1136R* | 968 | 855 | | Remote | 208-230/60/1 | 235 |

^{*} See Page 25 for Remote Condensers



| | Model Number | Ice Production lb/24 hr @ 70°F Air/50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Half / Full Cube | Condens- ing Unit | Voltage Units | Ship Weight (lbs) |
|--|-----------------|---|--|------------------------|----------------------|------------------|-------------------------|
| | CIM1446A | 1600 | 1174 | | Air | 208-230/60/1 | 310 |
| | CIM1446W | 1560 | 1397 | | Water | 208-230/60/1 | 300 |
| | CIM1446R* | 1650 | 1300 | | Remote | 208-230/60/1 | 280 |
| | CIM1447A | 1550 | 1174 | | Air | 208-230/60/3 | 310 |
| | CIM1447W | 1565 | 1397 | | Water | 208-230/60/3 | 300 |
| | CIM1447R* | 1625 | 1290 | H/F | Remote | 208-230/60/3 | 280 |
| | CIM2046W | 1860 | 1690 | | Water | 208-230/60/1 | 335 |
| | CIM2046R* | 1830 | 1533 | | Remote | 208-230/60/1 | 335 |
| | CIM2047W | 1860 | 1639 | | Water | 208-230/60/3 | 325 |
| | CIM2047R* | 1830 | 1533 | | Remote | 208-230/60/3 | 335 |

^{*} See Page 25 for Remote Condensers


^{**} Grande Cube

${\sf ELEVATION}\ {\sf SERIES^{\tiny\sf TM}}\ |\ {\sf Modular}\ {\sf Ice}\ {\sf Makers}$

| Model Number | Description | Ship Weight (lbs) |
|--------------|---|-------------------|
| BPF-1 | Filler Panel Kit with 30" CIM and ICE Series™ Cube Ice Makers for B110 bins only | 8 |
| KBT5 | Bin Top for 30" CIM and ICE Series Cube Ice Makers including the ICE1506 family for B100 bin | 30 |
| KBT23 | Bin Top for (1) 22" CIM Series Ice Makers on a B110 bin | 22 |
| KBT222 | Bin Top for (2) 22" CIM Series Ice Makers on a B110 bin | 33 |
| KCFS9-22* | Mounting kit for Coca-Cola Freestyle 9000 with 22" CIM Series Ice Cube Makers | 5 |
| KCFS91-22* | Mounting kit for Coca-Cola™ Freestyle 9100 with 22" CIM Series Ice Cube Makers | 5 |
| KCFS71-30* | Mounting kit for Coca-Cola™ Freestyle 7000/7100 with 30" CIM Series Ice Cube Makers | 5 |
| KCFS9-30* | Mounting kit for Coca-Cola™ Freestyle 9000 with 30" CIM Series Ice Cube Makers | 10 |
| KCFS91-30* | Mounting kit for Coca-Cola™ Freestyle 9100 with 30" CIM Series Ice Cube Makers | 5 |
| KCUBEDISP | Bin-level kit for Cornelius and Lancer dispensers with all CIM Series including the ICE1506 Ice Cube Makers | 1 |

 $^{^*}$ Adapter from Coca-Cola[™] also required.

^{**} Additional adapter may be required from dispenser manufacturer



Food Zone Disassembly and Cleaning

Incorporate FoodZone disassembly into your daily cleaning procedure for maximum machine uptime and food cleanliness



Loosen the two screws on the bottom of the front panel.



Remove the top plastic cover.





Remove the water hose.



Remove the evaporator splash plate.



Remove the distribution tube, depressing both side tabs.




Completely disassemble the distribution tube.



Swing up and depress the curtain's tabs to remove.




Remove the water reservoir by sliding out, down, and out.




All food zone parts are high temp dishwasher safe.

Pearl Ice® Series™ Modular Ice Makers



| Model Number | Ice Production Ibs/24 hr @ 70°F Air/ 50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-------------------|---|--|--------------------|---------------|-------------------------|
| ≅ GEM0450A | 464 | 353 | Air | 115/60/1 | 150 |
| GEM0450W | 508 | 429 | Water | 115/60/1 | 150 |
| GEM0650A | 740 | 500 | Air | 115/60/1 | 150 |
| GEM0650W | 770 | 633 | Water | 115/60/1 | 165 |
| GEM0650R* | 770 | 550 | Remote | 115/60/1 | 175 |
| GEM0650R49* | 763 | 581 | Remote | 115/60/1 | 175 |
| ≅ GEM0956A | 1053 | 753 | Air | 208-230/60/1 | 165 |
| GEM0956W | 1053 | 877 | Water | 208-230/60/1 | 220 |
| GEM0956R* | 1011 | 820 | Remote | 208-230/60/1 | 230 |
| GEM0956R49* | 932 | 695 | Remote | 208-230/60/1 | 230 |
| GEM1306A | 1350 | 1000 | Air | 208-230/60/1 | 220 |
| | 1350 | 1000 | Remote | 208-230/60/1 | 240 |
| GEM1306R49* | 1240 | 947 | Remote | 208-230/60/1 | 240 |



| | Model Number | Ice Production lbs/24 hr @ 70°F Air/ 50°F Water | Ice Production lbs/24 hr @ 90°F Air/70°F Water | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|---|--------------------|---|--|--------------------|---------------|-------------------------|
| | ⊆ GEM2006R* | 1960 | 1635 | Remote | | |
| " | GEM2006R49* | 1780 | 1470 | Remote | 208-230/60/1 | 316 |
| | GEM2006W | 2225 | 1850 | Water | | |
| | Ouglifies for End | aray Star | | | | |

Qualifies for Energy Star

Pearl Ice® Series™ Accessories

| Model Number | Description | Ship Weight (lbs) |
|--------------|---|-------------------|
| BPF-1 | Filler Panel Kit with 30" GEM Series Ice® Makers for B110 bins only | 8 |
| KBT5 | Bin Top for 30" GEM Series Ice® Makers on a B100 bin | 30 |
| KBT19 | Bin Top for 21" GEM Series Ice® Makers on a 30" bin | 22 |
| KBT222 | Bin Top for (2) GEM Series Ice® Makers on a B110 bin | 33 |
| KBT23 | Bin Top for (1) GEM Series Ice® Makers on a B110 bin | 33 |
| KBT24 | Bin Top for (1) GEM Series Ice® Makers on a 22" bin | 10 |
| KBTF230 | Bin Kit for (2) 30" GEM Series Ice® Makers on 60" bins only | 1 |
| KGEMDISP | Kit required when mounting GEM Series Ice® Makers to beverage dispenser | 1 |
| KGEMFS* | Mounting and bin level ice control kit, required for installation of 21" GEM Series Ice® Makers on Coca-Cola™ Freestyle dispenser model 9000. | 5 |
| KFS7-G* | Ice Control Kit, required for installation of 21" GEM Series Ice® Makers on a Coca-Cola™ Freestyle dispensers model 7000. | 5 |

^{*} Requires Coke adapter to match freestyle dispenser color.

^{*} See Page 24 & 25 for Remote Condensers

Pearl Ice® Series™ Ice-Water Dispenser



| Model Number | Ice Production Ibs/24 hr @ 70°F Air/ 50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Pearl Ice | Bin Storage (lbs) | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|---|--|--------------|-------------------------|--------------------|------------------|-------------------------|
| GEMD270A2 | 273 | 198 | Р | 12 | Air | 115/60/1 | 161 |

Pearl Ice® Series™ Ice-Undercounter Ice Maker



| Model Number | Ice Production lbs/24 hr @ 70°F Air/ 50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Pearl Ice | Bin Storage (lbs) | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|---|--|--------------|-------------------------|--------------------|------------------|-------------------------|
| GEMU090* | 85 | 60 | Р | 22 | Air | 115/60/1 | 133 |

^{*} Unit includes cord sets

Pearl Ice® Series™ Ice Maker & Ice Water Dispenser Accessories

| Model Number | Description | Ship Weight (lbs) |
|--------------|----------------------|-------------------|
| KPU090 | Pump kit for GEMU090 | 7 |

A consumer favorite.

It's a soft, chewable ice that absorbs the flavor of a beverage for more enjoyable chewing. This ice dispenses well, blends quickly and displaces liquid better than cubes. It's a great choice for restaurants, convenience stores and is ideal for use in buffets, grocery stores, fish markets, chilled food displays and it packs well for healthcare applications.






Perfect for presentation.


Our flake ice is ideal for both the presentation and preservation of perishable food items. Ice-O-Matic flake ice extends the shelf life and appearance of seafood, fresh fruits and vegetables for fresher displays that help increase sales. Flake ice is also ideal for use for perishable food transport and health care applications.



Flake Ice Series Modular Ice Makers



| Model Number | Ice Production Ibs/24 hr @ 70°F Air/ 50°F Water | Ice Production Ibs/24 hr @ 90°F Air/70°F Water | Condensing Unit | Voltage Units | Ship Weight (lbs) |
|-----------------|---|--|--------------------|---------------|-------------------------|
| MFI0500A | 540 | 370 | Air | 115/60/1 | 205 |
| MFI0500W | 541 | 456 | Water | 115/60/1 | 205 |
| MFI0800A | 900 | 615 | Air | 115/60/1 | 200 |
| MFI0800W | 940 | 740 | Water | 115/60/1 | 200 |
| MFI0800R* | 925 | 650 | Remote | 115/60/1 | 200 |
| MFI1256A | 1149 | 885 | Air | 208-230/60/1 | 215 |
| MFI1256W | 1137 | 959 | Water | 208-230/60/1 | 210 |
| MFI1256R* | 1040 | 950 | Remote | 208-230/60/1 | 230 |
| MFI1256R49* | 1035 | | Remote | 208-230/60/1 | 230 |
| MFI1506A | 1450 | 1050 | Air | 208-230/60/1 | 290 |
| ■ MFI1506R* | 1390 | 1025 | Remote | 208-230/60/1 | 290 |
| MFI1506R49* | 1375 | 1018 | Remote | 208-230/60/1 | 290 |



| Model Number | Ice Production Ibs/24 hr @ 70°F Air/ 50°F Water | lce Production lbs/24 hr @ 90°F Air/70°F Water | Condensing Unit | Voltage Units | Ship Weight (lbs) | |
|---------------------------|---|--|--------------------|---------------|-------------------------|--|
| MFI2306R* | 2250 | 1845 | Remote | | | |
| MFI2306R49* | 2100 | 1709 | Remote | 208-230/60/1 | 316 | |
| MFI2306W* | 2600 | 2100 | Water | | | |
| Qualifies for Energy Star | | | | | | |

Flake Ice Series Accessories

| Model Number | Description | Ship Weight (lbs) |
|--------------|--|-------------------|
| BPF-1 | Filler Panel Kit with 30" MFI Series Ice Makers for B110 bins only | 8 |
| KBT5 | Bin Top for 30" MFI Series Ice Makers on a B100 bin | 30 |
| KBT19 | Bin Top for 21" MFI Series Ice Makers on a 30" bin | 22 |
| KBT222 | Bin Top for (2) MFI Series Ice Makers on a B110 bin | 33 |
| KBT23 | Bin Top for (1) MFI Series Ice Makers on a B110 bin | 33 |
| KBT24 | Bin Top for (1) MFI Series Ice Makers on a 22" bin | 10 |
| KBTF230 | Bin Kit for (2) 30" MFI Series Ice Makers on 60" bins only | 1 |
| KGEMDISP | Kit required when mounting MFI to beverage dispenser | 1 |
| KGEMFS* | Mounting and bin level ice control kit, required for installation of 21" MFI Series Ice Makers on Coca-Cola™ Freestyle dispenser model 9000. | 5 |
| KFS7-G* | Ice Control Kit, required for installation of 21" MFI Series Ice Makers on a Coca-Cola™ Freestyle dispensers model 7000. | 5 |


^{*} Requires Coke Adapter to match Freestyle dispenser color

^{*}See Page 25 for Remote Condensers.

Remote Condensers




| Model Number | Description | Voltage Units | Ship Weight (lbs) |
|-----------------|---|---------------|----------------------|
| RC100G49 | Remote Condenser for model GEM0650R49 | 115/60/1 | 90 |
| RC106G49 | Remote Condenser for models GEM0956R49, GEM1306R49, MFI1256R49, and MFI1506R49 | 208-230/60/1 | 90 |
| RC100C49 | Remote Condenser for CIM0530R49 | 115/60/1 | 91 |
| RC106C49 | Remote Condenser for model CIM0636R49 | 208-230/60/1 | 97 |
| RC206C49 | Remote Condenser for models CIM0826R49, CI- M0836R49, CIM1126R49, and CIM1136R49 | 208-230/60/1 | 108 |
| RC306C49 | Remote Condenser for models CIM1446R49, GEM2006R49, MFI2306R49, and ICE1506R49 | 208-230/60/1 | 122 |
| RC406C49 | Remote Condenser for model CIM2046R49 | 208-230/60/1 | 138 |







Remote Condensers



| Model Number | Description | Voltage Units | Ship Weight (lbs) |
|-----------------|---|---------------|----------------------|
| RC100G40* | Remote Condenser for models GEM0650R, and MFI0800R | 115/60/1 | 90 |
| RC106G40* | Remote Condenser for models GEM0956R, GEM1306R, MFI1506R, and MFI1256R | 208-230/60/1 | 90 |
| RC100C40 | Remote Condenser for CIM0530R | 115/60/1 | 91 |
| RC106C40 | Remote Condenser for model CIM0636R | 208-230/60/1 | 97 |
| RC206C40 | Remote Condenser for models CIM0826R, CIM0836R, CIM1126R, and CIM1136R | 208-230/60/1 | 108 |
| RC306C40 | Remote Condenser for models CIM144*R, GEM2006R and MFI2306R | 208-230/60/1 | 122 |
| RC406C40 | Remote Condenser for model CIM204*R | 208-230/60/1 | 138 |





| Model Number | Description | Previous Model | Voltage Units | Ship Weight (lbs) |
|-----------------|-------------------------------------|-------------------|---------------|----------------------|
| RCA3061 | Remote Condenser for model ICE1506R | N/A | 208-230/60/1 | 107 |

^{*} Does not include Headmaster

Remote Condenser Accessories

| Model Number | Description | Ship Weight (lbs) |
|--------------|---|----------------------|
| RL404-25 | 25 ft. Precharged Tubing Kit for units using R-404A refrigerant | 13 |
| RL404-40 | 40 ft. Precharged Tubing Kit for units using R-404A refrigerant | 18 |
| RL404-75 | 75 ft. Precharged Tubing Kit for units using R-404A refrigerant | 36 |
| RL49-25 | 25 ft. Precharged Tubing Kit for units using R-449A refrigerant | 13 |
| RL49-40 | 40 ft. Precharged Tubing Kit for units using R-449A refrigerant | 18 |
| RL49-75 | 75 ft. Precharged Tubing Kit for units using R-449A refrigerant | 36 |
| KRL-25 | 25 ft. Noncharged Tubing Kit, includes insulated tubing and couplings, brazing required | 13 |
| KRL-40 | 40 ft. Noncharged Tubing Kit, includes insulated tubing and couplings, brazing required | 18 |
| KRL-75 | 75 ft. Noncharged Tubing Kit, includes insulated tubing and couplings, brazing required | 36 |

Countertop Cube/Pearl Ice Dispensers



| Model Number | Dispenser Operation | Bin Storage (lbs) | Voltage Units | Ship Weight (lbs) |
|--------------|---------------------|-------------------|---------------|----------------------|
| IOD150* | Cup Activated | 150 | 115/60/1 | 139 |



| Model Number | Dispenser Operation | Bin Storage (lbs) | Voltage Units | Ship Weight (lbs) |
|--------------|---------------------|-------------------|---------------|----------------------|
| IOD200** | Cup Activated | 200 | 115/60/1 | 193 |
| IOD250** | Cup Activated | 250 | 115/60/1 | 197 |

Hotel Cube Ice Dispensers



| Model Number | Dispenser Operation | Bin Storage (lbs) | Voltage Units | Ship Weight (lbs) |
|--------------|---------------------|-------------------|---------------|----------------------|
| CD40022* | Push Activated | 120 | 115/60/1 | 230 |



| Model Number | Dispenser Operation | Bin Storage (lbs) | Voltage Units | Ship Weight (lbs) |
|---|-------------------------|-------------------|---------------|----------------------|
| CD40030** | Push Activated | 100 | 115 /60 /1 | 220 |
| CD40130** Water Glass Filler Kit Included | Push & Cup Activated | 180 | 115/60/1 | 230 |

^{*} Accepts only 22" Machines

^{**} Accepts only 30" Machines

Ice Dispenser & Hotel Accessories

| Model Number | Description | Ship Weight (lbs) |
|--------------|--|-------------------|
| KBT15022 | Adapter and bin-level kit for 22" cubers and nugget ice makers on IOD150 | 12 |
| KBT25022 | Adapter and bin-level kit for 22" cubers and nugget ice makers on IOD200/250 | 28 |
| KBT25030 | Adapter and bin-level kit for 30" cubers on IOD200/250 | 13 |
| KWGFID | Water glass filler kit for IOD150/200/250 and CD40022 (Field installed only) | 2 |
| KGEMDISP | Kit required when mounting GEM to beverage dispenser | 1 |
| KCUBEDISP | Bin-level kit for Cornelius and Lancer dispensers with 30" CIM Series Cube Ice Makers (Bin stat & deflector included) | 1 |
| KFS7-22* | Mounting kit for Coca-Cola™ Freestyle7000 & 7100 with 22" ICE Series Cube Ice Makers | 9 |
| KFS7-30* | Mounting kit for Coca-Cola™ Freestyle 7000 & 7100 with 30" ICE Series Cube Ice Makers | 10 |
| KCFS71-30* | Mounting kit for Coca-Cola™ Freestyle 7000 & 7100 with 30" CIM Series Cube Ice Makers | 7 |
| KCFS9-22* | Mounting kit for Coca-Cola™ Freestyle 9000 with 22" CIM Series Cube Ice Makers | 5 |
| KCFS91-22* | Mounting kit for Coca-Cola™ Freestyle 9100 with 22" CIM Series Cube Ice Makers | 5 |
| KCFS91-30* | Mounting kit for Coca-Cola™ Freestyle 9100 with 30" CIM Series Cube Ice Makers | 14 |
| KCFS9-30* | Mounting kit for Coca-Cola™ Freestyle 9000 with 30" CIM Series Cube Ice Makers | 10 |
| KGEMFS* | Mounting and bin level ice control kit, required for installation of 22" Pearl Ice Makers on Coca-Cola™ Freestyle dispenser model 9000. Requires Coca-Cola™ Adapter to match Freestyle dispenser (red, silver, or black) | 5 |

 $^{^{\}ast}~$ Adapter from Coca-Cola $^{\scriptscriptstyle{\mathsf{TM}}}$ also required.

Dispenser Kits

| Model Style | | CIM Series Cube Ice Makers | | ICE Series Cube Ice Makers | | GEM Series Ice Makers | |
|----------------------|------------------------------------|----------------------------|-----------|----------------------------|-----------|-----------------------|----------|
| Number | | 22" W | 30" W | 22" W | 30" W | 21" W | 30" W |
| IOD150 | 22" Countertop Dispenser | KBT15022 | N/C | KBT15022 | N/C | KBT15022 | N/C |
| IOD200/250 | 30" Countertop Dispenser | KBT25022 | KBT25030 | KBT25022 | KBT25030 | KBT25022 | KBT25030 |
| GENERIC DISPENSER | Lancer/Serv-end Etc. | KCUBEDISP | KCUBEDISP | KCUBEDISP | KCUBEDISP | KGEMDISP | KGEMDISP |
| CD40022 | 22" Hotel Dispenser | A | N/C | A | N/C | N/C | N/C |
| CD40030 | 30" Hotel Dispenser | N/C | A | N/C | A | N/C | N/C |
| FS7000 | 30" Countertop Coke Dispenser | KCUBEDISP | KFS71-30 | KFS7-22 | KFS7-30 | KFS7-G | N/C |
| FS7100 | 30" Countertop Coke Dispenser | KCUBEDISP | KFS71-30 | KFS7-22 | KFS7-30 | KFS7-G | N/C |
| FS9000 | 22" Freestanding Coke Dispenser | KCFS9-22 | KCFS9-30 | KIBD-01 | KIBD-30 | KGEMFS | N/C |
| FS9100 | 22" Freestanding Coke Dispenser | KCFS91-22 | KCFS91-30 | KFS91-22 | KIBD91-30 | KGEMDISP | N/C |
| PEPSI SPIRE | 30" Countertop Pepsi Dispenser | KCUBEDISP | KCUBEDISP | KCUBEDISP | KCUBEDISP | KGEMDISP | KGEMDISP |

This information is subject to change. Please visit our website **www.iceomatic.com** for the most recently updated kit information. ▲ Kit not required

N/C - Ice Machine and Dispenser not compatible.

Storage Bins

| Model Number | Bin Storage (lbs) | Dimensions W x D x H (in) | Ship Weight (lbs) |
|--------------|-------------------|---------------------------|-------------------|
| B40 | 344 | 30 x 31 x 28 | 103 |
| B42 | 351 | 22 x 31 x 50 | 99 |
| B55 | 510 | 30 x 31 x 50 | 125 |
| B110 | 854 | 48 x 31 x 50 | 191 |









Bin Top Adapters

| Model Number | Description | Ship Weight (lbs) |
|--------------|--|----------------------|
| KBT5 | Bin Top for 30" CIM and ICE Series Cuber including the ICE1506 family for B100 only | 30 |
| KBT19 | Bin Kit for 22" CIM, MFI and GEM Series on a 30" bin | 22 |
| KBT222 | Bin top for (2) 22" CIM, (2) MFI or (2) GEM Series on B110 bin | 33 |
| KBT23 | Bin Kit for (1) 22" CIM, (1) GEM or (1) MFI Series on a B110 bin | 33 |
| KBT24 | Bin Kit for (1) GEM or (1) MFI on a 22" bin | 10 |
| KBTF230 | Bin Kit for (2) 30" CIM, GEM and MFI Series Cube Ice Makers on 60" bins only | 43 |
| KBTF21506 | Bin for for (2) 30" ICE1506 on 60" bin only | 43 |
| BPF-1 | Filler Panel Kit with 30" CIM, GEM, MFI and ICE Series™ Cube Ice Makers for B110 bins only | 8 |

| Model Number | Description | Ship Weight (lbs) |
|--------------|------------------|----------------------|
| KLSCO | 82 oz ice scoop* | 1 |
| KSSCO | 16 oz ice scoop* | 1 |
| KSHOV | Plastic shovel | 3 |
| KSHOB | Bracket shovel | 2 |
| KICEP | Plastic paddle | 7 |
| KPBRA | Bracket paddle | 2 |

^{*} Ice scoop sold separately for B700-30, B1000-48, B1300-48, B1325-60 and B1600-60 models.

Single Ice Machine Configurations

| Model | | CIM Series Cube Ice Makers | | | ICE Series Cube Ice Makers | | | Pearl Ice® Ice Makers | | Flake Ice Makers | |
|----------|-------------|----------------------------|----------|----------|----------------------------|----------|----------|-----------------------|----------|------------------|----------|
| Number | Style | 22" W | 30" W | 48" W | 22" W | 30" W | 48" W | 21" W | 30" W | 21" W | 30" W |
| B40 | Slope Front | KBT19 | A | N/C | KBT19 | A | N/C | KBT19 | A | KBT19 | A |
| B42 | Slope Front | A | N/C | N/C | A | N/C | N/C | KBT24 | N/C | KBT24 | N/C |
| B55 | Slope Front | KBT19 | A | N/C | KBT19 | A | N/C | KBT19 | A | KBT19 | A |
| B110 | Slope Front | KBT23 | BPF-1* | A | KBT23 | BPF-1* | A | KBT23 | BPF-1* | KBT23 | BPF-1* |
| B700-30 | Upright | A | A | N/C | A | A | N/C | A | A | A | A |
| B1000-48 | Upright | A | A | A | A | A | A | A | A | A | A |
| B1300-48 | Upright | A | A | A | A | A | A | A | A | A | A |
| B1325-60 | Upright | A | A | A | A | A | A | A | A | A | A |
| B1600-60 | Upright | A | A | A | A | A | A | A | A | A | A |

^{*} BPF-1 used with B110 bins only. If you have an older model B100 use the KBT5.

Side-By-Side Ice Machine Configurations

| Model | | CIM Series Cube Ice Makers | | ICE Series C | ICE Series Cube Ice Makers | | Pearl Ice® Ice Makers | | Flake Ice Makers | |
|--------------|-------------|----------------------------|-----------|--------------|----------------------------|-----------|-----------------------|-----------|------------------|--|
| Number Style | 2 x 22" W | 2 x 30" W | 2 x 22" W | 2 x 30" W | 2 x 21" W | 2 x 30" W | 2 x 21" W | 2 x 30" W | | |
| B40 | Slope Front | N/C | N/C | N/C | N/C | N/C | N/C | N/C | N/C | |
| B42 | Slope Front | N/C | N/C | N/C | N/C | N/C | N/C | N/C | N/C | |
| B55 | Slope Front | N/C | N/C | N/C | N/C | N/C | N/C | N/C | N/C | |
| B110 | Slope Front | KBT222 | N/C | N/C | KBT222 | KBT222 | N/C | KBT222 | N/C | |
| B700-30 | Upright | N/C | N/C | N/C | N/C | N/C | N/C | N/C | N/C | |
| B1000-48 | Upright | A | N/C | A | N/C | A | N/C | A | N/C | |
| B1300-48 | Upright | A | N/C | A | N/C | A | N/C | A | N/C | |
| B1325-60 | Upright | A | KBTF230 | A | KBTF21506 | A | KBTF230 | A | KBT230 | |
| B1600-60 | Upright | A | KBTF230 | A | KBTF21506 | A | KBTF230 | A | KBT230 | |

▲ Kit not required

N/C - Ice Machine and Bin Configurator not compatible

There are times when it is desirable to install (2) ice machines side-by-side on a bin. The reasons may range from gaining maximum output to creating redundancy. Ice-O-Matic offers on array of kits and bins with custom order tops for just such applications.

[▲] Kit not required / N/C - Ice Machine and Bin Configurator not compatible

Water Filtration Systems



IFQ1-S Single Filter

| dimensions (in) | 10.4 x 6 x 4 |
|-------------------------|--------------|
| flow rate max (gpm) | .75 |
| pressure max (psi) | 125 |
| max operating temp (°F) | 100 |
| micron rating | 2 |
| ship weight (lbs) | 2 |
| pack quantity | N/A |



IFQ1 Single Filter

| dimensions (in) | 15 x 6 x 4 |
|-------------------------|------------|
| flow rate max (gpm) | 1.5 |
| pressure max (psi) | 125 |
| max operating temp (°F) | 100 |
| micron rating | 2 |
| ship weight (lbs) | 4 |
| pack quantity | 10 |



IFQ1-XL Single Filter

| dimensions (in) | 21 x 6 x 4 |
|-------------------------|------------|
| flow rate max (gpm) | 2.25 |
| pressure max (psi) | 125 |
| max operating temp (°F) | 100 |
| micron rating | 2 |
| ship weight (lbs) | 5 |
| pack quantity | N/A |



IFQ2 **Dual Filter**

| dimensions (in) | 16 x 10 x 7.125 |
|-------------------------|-----------------|
| flow rate max (gpm) | 3 |
| pressure max (psi) | 125 |
| max operating temp (°F) | 100 |
| micron rating | 2 |
| ship weight (lbs) | 8 |
| pack quantity | N/A |



IFQ2-XL Dual Filter

| dimensions (in) | 23.21 x 13 x 4.65 |
|-------------------------|-------------------|
| flow rate max (gpm) | 4.5 |
| pressure max (psi) | 125 |
| max operating temp (°F) | 100 |
| micron rating | 2 |
| ship weight (lbs) | 9 |
| pack quantity | N/A |



IFI4C / IFI8C
Single Inline Cartridge .25" Compression
(IFI4C) or .375" Compression (IFI8C)

| dimensions (in) | 11.75 x 2.75 |
|-------------------------|--------------|
| flow rate max (gpm) | 1.0 |
| pressure max (psi) | 100 |
| max operating temp (°F) | 100 |
| micron rating | 10 |
| ship weight (lbs) | 2 |
| pack quantity | 12 |

IOM Replacement Cartridges

| Model Number | Description | Pack Gty |
|--------------|--|----------|
| IOMQ-S | Single quick twist replacement cartridge for IFQ1-S | N/A |
| IOMQ | Single quick twist replacement cartridge for IFQ1 or IFQ2 | 10 |
| IOMQ-XL | Single quick twist replacement cartridge for IFQ1-XL | N/A |
| IOMWFRC | Single replacement filter with male quick connect fittings for manifold filter systems | 10 |

Filter Cartridge Features

- Inhibit the formation of scale
- Remove dirt and sediment
- Reduce chlorine, taste and odor

Ice-O-Matic recommends the use of water filtration with all ice-making products.

Water Filtration Application Charts - CUBE

| Model Number | ICEU070 | ICEU150 ICEU220 ICEU300 | CIM0320- CIM0430 | CIM0520- CIM0630 | CIM0826- CIM1136 | CIM1446- CIM1545 | CIM1845- CIM2046 | ICE1506 | UCG080- UCG130 |
|-----------------|---------|-------------------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------|-------------------|
| IFQ1-S | X | X | | | | | | | Χ |
| IFQ1 | | | Χ | | | | | | |
| IFQ1-XL | | | | X | | | | | |
| IFQ2 | | | | | X | X | | X | |
| IFQ2-XL | | | | | | | X | | |
| IFI4C / IFI8C | X | X | | | | | | | Χ |

Water Filtration Application Charts - PEARL & FLAKE

| Model Number | GEMU090 | GEM0450- GEM0650 | GEM0956 | GEM1306 | GEM2006 | MFI0500 | MFI0800- MFI1256 | MFI1506 | MFI2306 |
|-----------------|---------|---------------------|---------|---------|---------|---------|---------------------|---------|---------|
| IFQ1-S | Χ | | | | | Χ | | | |
| IFQ1 | | Χ | | | | | | | |
| IFQ1-XL | | | X | | | | X | | |
| IFQ2 | | | | X | | | | X | |
| IFQ2-XL | | | | | X | | | | Χ |
| IFI4C / IFI8C | X | | | | | X | | | |



Use the QR Code above for our most current list prices.

Ice-O-Matic's knowledgeable sales representatives can also answer any questions and walk you through the selection process.

Contact Us.

SALES AND CUSTOMER SERVICE

Whether you have a sales question, a support inquiry, or just need to hear a friendly voice our outstanding customer service is available for you.

Call Us: 1-800-423-3367

Online: iceomatic.com/servicesupport

Email Us: customer.experience@iceomatic.com

TECHNICAL SUPPORT 24/7 SUPPORT

Our technical support center provides best-in-class service with decades of experience. Contact day or night with your most technical questions!

Call Us: 1-855-TECH-IOM

Online: iceomatic.com/servicesupport

Email Us: techsupport@iceomatic.com





Scan QR code above for digital copy

11100 East 45th Avenue | Denver, CO 80239 866.PUREICE | iceomatic.com Updated: October 2025