

NE-21523

2100 WATT* COMMERCIAL MICROWAVE OVEN

FOOD SERVICE EQUIPMENT

PRO1www.panasonic.com/CMO

UPGRADE YOUR PERFORMANCE with PRO1:

Quickly achieve delicious, consistent product your clients will love in a fraction of time.

- **Higher Wattage:** Quicker, more efficient operation—and better retains foods' nutrients!
- **Programmable:** Same flavorful outcome every time
- **Additional Power Levels and Multi-stage Cooking:** Best showcase flavor in food
- Enhanced diagnostics, enhanced heating elements
- Auto voltage switching

	NE-21521 / NE-21523
Power Source:	208/230-240V, 60Hz, Single Phase
Receptacle Required:	NEMA 6-20
Frequency:	2,450MHz
Required Power:	208V (16.3A), 230-240V (14.9A)
Output:	2100 Watts*
Outer Dimensions: (w x d x h)	16-5/8" x 20" x 13-1/8"
Cavity Dimensions: (w x d x h)	13" x 12" x 6-1/8"
Net Weight:	68 lbs.
Shipping Weight:	72 lbs.
Shipping Box Size: (w x d x h)	19-15/16" x 24-1/8" x 16-7/8" 4.7 cu. ft.
Timer:	Maximum times for each stage of cooking: Times vary for each (of 15) power levels (See Manual)
Memory Capability:	30 Programs

The NE-21523 commercial microwave meets or exceeds all safety performance and sanitation standards set for commercial food service microwave ovens by UL, HHS, FCC and NSF.



Panasonic Commercial Food Service
Division of Panasonic Corporation of North America
2 Riverfront Plaza | Newark, NJ 07102
(201) 348-7000
www.panasonic.com/cmo

PERFECT FOR

- Quick serve and casual dining applications
- Chef's line
- Over shelf
- High volume application where space is at a premium
- Fast 1/2 pan cooking/re-therm

PERFORMANCE

- 2100 Watt power
- 15 Power levels
- 30 memory capability
- 5-stage cooking
- Controllable LED lights
- 2 magnetrons (heating elements)
- One-Touch start feature
- Independent top/bottom energy feed control
- Auto voltage switching

ADDITIONAL FEATURES

- 0.6 cubic feet capacity
- 16-5/8" wide
- Fits 1 half-size 6" deep steam table pan/cover
- Quick-clean stainless steel cabinet + cavity
- Compact size, heavy-duty performance
- Cycle counter
- Programmable lock
- Easy-clean air filter with reminder
- Patented safety door seal system
- See-through oven door
- Removable ceiling splatter shield
- Digital display
- Stackable

MAINTENANCE

- Enhanced diagnostics
- Warranty: 3 years parts and labor
3 years magnetron



*IEC 705 Test Procedure

