


Dual Hitch Extension Model No: 15954

*4000 lb Gross Trailer weight *400 lb Combined Tongue Weight

Serious injury or death may result from the use of this product. Exercise extreme caution when using this receiver.

- User must ensure product is installed according to these instructions. Purchaser, owner or user must not alter or modify the product.
- This Instruction Sheet contains IMPORTANT safety information. Please read, understand and keep for future reference.
- The proper attachment of this product in accordance with the enclosed instructions is critical to its proper performance. bROK Products has no control over nor any responsibility for the product's attachments and use. bROK Products is not responsible nor will be held liable for any damage resulting from its attachment, use or misuse. bROK Products shall not be liable for any claims of any kind greater than the purchase price of the Dual Hitch Extension unit.


- Read and follow all instructions and safety messages before using the Dual Hitch Extension.
- Inspect for signs of wear, rust and damage before each use, if damaged, DO NOT USE.
- Never tow using the accessory receiver. Only use the accessory receiver for non towing accessories (e.g. bike racks, cargo trays). The Dual Hitch Extension should be installed with the accessory receiver in the top or upright position.



- Do not exceed a gross trailer weight of 4,000 lb or a combined total tongue weight of 400 lb. The combined tongue weight includes the trailer tongue weight plus the total loaded weight of the accessories.
- Do not exceed your vehicle manufacturer's recommended towing capacity. Consult the owners manual of your vehicle.
- Do not use with weight distribution system.
- Do not attempt to cut, weld or modify in any way the Dual Hitch Extension.
- Do not use more than one extension
- Inspect your vehicle and trailer connections at each stop and before each use.

Installation Instructions

A NEVER tow using the accessory receiver. Only use this receiver for non-towing accessories such as bike racks and cargo trays. The Dual Hitch Extension should be installed with the accessory receiver in the top or upper most position.



- DO NOT EXCEED a gross trailer weight of 4,000 lb or a combined total tongue weight of 400lb. The combined tongue weight includes the addition of the trailer tongue weight plus the total loaded accessory weight.
- DO NOT exceed your vehicle manufacturer's recommended towing capacity. Consult your vehicle owner's manual.



DO NOT use more than one extension

No tools are required for the installation of the Dual Hitch Extension,

When in stalling the Dual Hitch Extension, check to ensure there is sufficient clearance between the tow vehicle, tongue, ground and/or any other mounted accessories while the vehicle is stationary or that may occur when driving. The Dual Hitch Extension must be installed with the Accessory receiver in the uppermost top position. A ball mount bar used in the rise position with the Dual Hitch Extension may cause interference. If this is the case, do not use the Dual Hitch Extension.

Check for interference once installation and loading is complete.

While Towing

To reduce the risk of serious injury or death to you, your passengers or others on the road:



A Reduce your speed. Slow down when towing. Always keep your speed under all posted speed limits. Be aware of and heed traffic and road condition Inspect your vehicle, trailer, all lights, and all connections at each stop.