COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

Portable Electric Rotary Compressor: Fixed Speed

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer: **Sample Compressor Inc.**		
2	Model Number: **12A 22B 40 - 125 psig / 460V/3ph/60Hz**	Date:	**8/12/2019**
	[X] Air-cooled [ ] Water-cooled	Type:	**Screw**
	[ ] Lubricated [ ] Oil Free	# of Stages:	**1**
3	Rated Capacity at Full Load Operating Pressure [a, e]	**175.0**	acfm [a,e]
4	Full Load Operating Pressure [b]	**125**	psig [b]
5	Maximum Full Flow Operating Pressure [c]	**125**	psig [c]
6	Drive Motor Nominal Rating	**40**	hp
7	Drive Motor Nominal Efficiency	**93.6**	percent
8	Fan Motor Nominal Rating (if applicable)	**1.3**	hp
9	Fan Motor Nominal Efficiency	**80**	percent
10	Total Package Input Power at Zero Flow [e]	**9.1**	kW [e]
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure [d]	**36.12**	kW [d]
12	Package Specific Power at Rated Capacity and Full Load Operating Pressure [e]	**18.69**	kW/100 cfm [e]
13	Isentropic Efficiency	**72.77**	Percent

Consult CAGI website for a list of section members: www.cagi.org

NOTES:

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
d. Total package input power at other than reported operating points will vary with control strategy.
e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m^3 / min	ft^3 / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	+/- 10%
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

CAGI Compressed Air & Gas Institute Member

Port B.1.1

8/26 Rev 1 This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.