



# FLEXIBLE FILTER

FILTER-KIT-FP, FILTER-KIT-FS, FILTER-KIT-FC

Designed to operate with any commercial fryer, this powerful and easy-to-use filtration system is an extremely functional extension to any frying system. With high-capacity filtration, you quickly benefit through longer and more consistent shortening life, as well as by reducing shortening waste.

## CONSTRUCTION AND FEATURES

- 100% heavy-gauge stainless steel construction
- Simplicity is key: Easy to assemble, use, and clean
- Disposable paper or carbon filter element or reusable stainless steel
- Factory assembled—or can be easily converted on site
- Specially designed, non “shearing” 5-gpm (90 l) pump with a 110 V 15 A - 250 V 3.5 A (1/2 HP motor)
- Seamless integration with Frontline International containment systems
- Power switch and safety “break away” power cord
- Stainless steel refill (wash down) nozzle
- Easy-to-use, quick-disconnect fittings
- Easy to clean with removable bucket
- UL and UL Sanitation Listed
- One-year warranty on all components



## Installation and Operating Specifications

Model	FILTER-KIT-FP, FILTER-KIT-FS, FILTER-KIT-FC
Power Requirements	110 V 15 A - 250 V 3.5 A, 50/60 Hz
Ship Wt. Kit Only	50 Lbs. (22.7 kg)
Ship Wt. w/10SS-NA*	170 Lbs. (77.1 kg)
Ship Wt. w/16SS-NA*	210 Lbs. (95.2 kg)
Ship Wt. w/20SS-NA*	220 Lbs. (99.8 kg)
Documentation	Conversion & Operating Instructions
Warranty	One-year parts and labor

\*Please refer to Transport Caddy spec sheets



### Frontline International, Inc.

187 Ascot Parkway • Cuyahoga Falls, Ohio 44223  
330-861-1100 • 877-776-1100 • frontlineii.com  
Fax: 330-861-1105 • info@frontlineii.com

**FRONTLINE**  
international

© Frontline International, 10/16